

Technical Data Sheet

ThimmTherm PFA Heating Cable

Technical Data Sheet

ThimmTherm PFA Heating Cable

44866 Bochum – Gewerbestr. 17
Tel.: (02327) 9837-0 Fax: (02327) 9837-20
e-mail: info@thimmtherm.de
Internet: <http://www.thimmtherm.de>



Technical Data Sheet

ThimmTherm PFA Heating Cable

Area of Application

Teflon-insulated and Teflon- sheathed industrial heating cables for heating pipe runs, containers and surfaces for frost protection and to maintain and increase temperature.

The heating cables are particularly suitable for use in the chemical industry because of their extreme resistance to corrosion, even when in direct contact with acids and bases.

Design features

Heating conductor:	Designed as flexible conductor with at least 7 individual wires, Resistance range 10...8000 Ohm/km. Tensile strength >120 N in accordance with VDE 0253/12.87, part 5.1.1. Materials used are in accordance with DIN 17 470 and 17 471.
Heating conductor	
Insulation material:	Material: Fluoropolymer, trade names TEFLON® or HOSTAFLO®N®, thickness of insulation 0,60 mm.
Serving:	Protective braid in accordance with VDE 0253/12.87, item 5.4, consisting of nickel-plated individual wires 0.16 m diameter. Minimum covering 70 %. Resistance <18.2 Ohm/km.
Sheath:	Material: Fluoropolymer. Alternatively: high-density polythene (HDPE). Trade name TEFLON® . Sheath wall thickness: 0.6 mm in accordance with VDE 0253.
Resistance range:	10..... 8000 Ohm per km
Diameter:	3.6..5.3 mm
Minimum bending radius:	2.5 times nominal diameter of heating cable.
Operating temperatures:	Maximum permissible temperature (continuous): 260° C.

